Tiedote

Schneider Electricin UPS Galaxy 300 tarjoaa tehokasta ja luotettavaa sähkönsyöttöä pienille ja keskisuurille organisaatioille

Luokkansa parhaat UPS-laitteet ovat yksinkertaisia asentaa, ylläpitää ja käyttää

Espoo, 17.5.2016 – Schneider Electric laajentaa Galaxy 300 UPS -häiriöttömän sähkönsyötön laitemallistoaan 60 kVA ja 80 kVA tehoisilla malleilla.

Uudet mallit on suunniteltu pienille ja keskisuurille yrityksille, toimistokiinteistöille sekä tuotantolaitoksille, joissa on pieni palvelinhuone tai muita toiminnalle elintärkeitä laitteistoja. UPS-laitteet tarjoavat kolmivaiheista virransuojausta korkealla hyötysuhteella liiketoimintakriittisille järjestelmille, joissa lyhytkin tuotantokatkos tai tietojen katoaminen voivat aiheuttaa merkittäviä vahinkoja. Energiatehokkuutensa ansiosta uudet UPS-järjestelmät pienentävät käyttö- ja jäähdytyskustannuksia.

Alkuperäinen tiedote:
Schneider Electric, a global specialist in energy management and automation, today announced the expansion of its Galaxy™ 300 uninterruptible power supply (UPS) system which now includes 60 kVA and 80 kVA models. Ideal for small and medium businesses, commercial buildings and technical facilities with small server rooms, the Galaxy 300 60 kVA and 80 kVA UPS systems provide effective and reliable three-phase power protection to prevent downtime and data loss for mission critical applications in a robust, simple-to-install and cost-effective configuration. The new UPS systems also enable users to lower operational and cooling costs with power efficiency and total harmonic distortion of current at less than 3.5 percent with full load.

“Our low- and medium-level power users and channel partners expressed a need for a system that offered greater power availability, reliability, manageability and convenience,” said Sam Wu, global product manager at Schneider Electric. “With the addition of the 60 kVA and 80 kVA models, the Galaxy 300 10 to 80 kVA UPS portfolio is now designed to serve a range of organizations while directly answering customer and partner needs by offering a best-in-class UPS with simplified installation, management and maintenance features, as well as enhanced efficiency and ease of use via an intuitive interface.”

To ensure uptime and availability, the Galaxy 300 10 to 80 kVA portfolio allows for standard installation of one or two independent power sources, and utilizes an online double conversion topology to provide true isolation between input and output with zero transfer time. A built-in 100 percent rated bypass static switch prevents interruption by allowing load transfer to utility power during heavy overloads. Connected equipment can be powered with two UPS unites in parallel to increase system redundancy. In addition, the system provides users with options for an integrated battery

Median yhteyshenkilö
Schneider Electric
Satu Kilpinen
050 588 5239
satu.kilpinen@schneider-electric.com

backup with up to 10 minutes of runtime or a robust charger for external batteries on rack or in external cabinets that provide run times of up to four hours.

Designed for ease-of-use, users are able to monitor and manage power requirements locally and remotely through a simple web/simple network management protocol interface. The simple-to-read and highly graphical user interface provides mimic diagrams, audible alarms and is available in 18 languages.

The Galaxy 300 10 to 80 kVA UPS systems are also equipped with several features that enable simple installation as well as tools to streamline compliance, maintenance and serviceability over the system's service life. An accessible maintenance bypass allows for complete isolation of each part of the system without power interruption, and the system features push-open door and slide out boards for effortless maintenance in confined spaces. For time-saving installation, the compact wide or narrow tower configurations can easily be rolled into new or existing facilities, and all wiring connections are easily identifiable. Step-by-step guidance and intuitive menu screens enable fast setup and system navigation.

Additional features of the systems include:

- A dual mains input that allows for stand installation of one or two independent power sources
- A power factor corrected input that prevents the need for oversizing cables, circuit breakers and generators
- Runtime options for UPS systems with integrated and external batteries
- Availability of three to three and three to single phase power configurations for convenient power distribution
- Restriction of the use of Hazardous Substances (RoHS) compliant

The Galaxy 300 10 to 80 kVA UPS systems are available via Schneider Electric channel partners and electrical contractors.

Tietoa Schneider Electricistä

Schneider Electric on maailmanlaajuinen energianhallinnan ja automaation asiantuntija. Vuonna 2015 yrityksen liikevaihto oli noin 27 miljardia euroa. Yrityksemme yli 160 000 työntekijää palvelevat asiakkaita yli 100 maassa ja auttavat heitä hallitsemaan energiaansa ja prosessejaan turvallisesti, luotettavasti, tehokkaasti ja kestävästi. Yksinkertaisimmista kytkimistä aina monimutkaisiin toimintajärjestelmiin asti teknologiamme, ohjelmistomme ja palvelumme auttavat asiakkaitamme hallitsemaan ja automatisoimaan toimintojaan paremmin. Kytketyt teknologiamme uudistavat teollisuudenaloja, muuttavat kaupunkeja ja rikastuttavat elämiämme.

Me Schneider Electricillä käytämme tästä sanontaa Life Is On.

Voit seurata meitä ja lukea lehdistötiedotteemme, ladata painokelpoisia kuvia ja tutkia lisämateriaalia uutishuoneessamme http://www.mynewsdesk.com/fi/schneider-electric-finland. Voit seurata meitä myös Twitterissä osoitteessa https://twitter.com/SchneiderEFI ja LinkedInissä osoitteessa https://www.linkedin.com/company/schneider-electric

www.schneider-electric.fi

Lisätietoja: Galaxy 300 -esitteet (englanniksi)

Median yhteyshenkilö
Schneider Electric
Satu Kilpinen
050 588 5239
satu.kilpinen@schneider-electric.com